

#### © 2013 American Foundry Society

Meets the Requirements of OSHA Standard 29 CFR 1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the Emergency Planning and Community Right-to-Know Act.

SAFETY DATA SHEET (SDS)

# **CARBON and ALLOY STEEL** CASTINGS

SDS SC-000-009 Rev. 16

**DATE ISSUED** 

10/13

# SECTION 1—PRODUCT IDENTIFICATION & COMPANY INFORMATION

#### PRODUCT NAME

# **CARBON and ALLOY STEEL CASTINGS**

OTHER DESIGNATIONS: ASTM (American Society for Testing & Materials) Specification No's., (ACI (Alloy Casting Institute) Alloy Designations— Grades)

ASTM No's.

A27-84

A128/A128M-84

A148/A148M-84

A216/A216M-84

A217/A217M-84

A352/A352M-84

A356/A356M-84

A426-80

A486/A486M-84

A487/A487M-84

A597/A597M-84

A660-79

A732/A732M-84

A757/A757M-84

SAE AUTOMOTIVE

J35C AAR

M201-81

**FEDERAL** 

QQ-S-681F

MIL-S-15083B (NAVY)

MIL-S-46052A (MR)

**ACI ALLOY DESIGNATIONS (GRADES)** 

N-1, N-2, U-60-30, 65-35, 70-36, 70-40

A, B-1, B-2, B-3, B-4, E-1, E-2, F

80-40, 80-50, 90-60, 105-85, 115-95, 135-125, 150-135, 160-145, 165-150, 165-150L,

210-180,210-180L, 260-210, 260-210L

WCA, WCB, WCC

WC1, WC5

LCA, LCB, LCC, LC1

1, 2, 5

CP1, CP2, CP15

70, 90, 120

1N, 2N, 4N, 6N, A, AN, B, BN, C, CN, DN, 1Q, 2Q, 4Q, 4QA, 6Q, AQ, BQ, CQ

CS-5

WCA, WCB, WCC

1A, 2A, 2Q, 3A, 3Q, 4A, 4Q, 5N, 6N, 13Q, 14Q

A1Q, A2Q

0022, 0025, 0030, 0050A, 0050B, 080, 090, 0105, 0120, 0150, 0175

A, B, C, D, E

N-1, N-2, U-60-30, 60-30, 65-35, 70-36, 70-40, 80-40, 80-50, 90-60, 105-85, 120-95, 150-

125, 175-135

**MILITARY STANDARD** 

CW, B, 65-35, 70-36, 80-40, 80-50, 90-60, 105-85, 120-95, 150-125

180-150, 220-180, 260-210

# **PRODUCT IDENTIFICATION (Label Identifier)**

Carbon and Alloy Steel Castings

MANUFACTURER'S NAME	STREET ADDRESS
Sawbrook Steel LLC	425 Shepherd Ave.
EMERGENCY TELEPHONE NO.	MAILING ADDRESS
513-554-1700	P.O. Box 15527
TELEPHONE NO.	CITY, STATE, ZIP CODE, COUNTRY
513-554-1700	Cincinnati, OH. 45215-0527 USA
FAX NO.	E-MAIL ADDRESS/WEBSITE
513-554-0092	sales@sawbrooksteel.com / www.sawbrooksteel

## RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Solid casting; no restrictions

## **SECTION 2—HAZARD IDENTIFICATION**

## CLASSIFICATION

Castings are metallic articles that do not present hazards in their original form.

#### OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 for further information.

SECTION 3—COMPOSITION/INFORMATION ON INGREDIENTS		
CHEMICAL NAME/COMMON NAME/SYNONYM	Wt %	CAS NUMBER
Carbon (C)	0–1.45	7440-44-0
Chromium (Cr)	0-0.90	7440-47-3
Iron (Fe)	Remainder	7439-89-6
Manganese (Mn)	0-14.0	7439-96-5
Molybdenum (Mo)	0–2.1	7439-98-7
Nickel (Ni)	0–1.0	7440-02-0
Silicon (Si)	0-2.25	7440-21-3

#### **SECTION 4—FIRST AID MEASURES**

**EYE CONTACT:** Not applicable

SKIN CONTACT: No special requirements

INGESTION: Not applicable
INHALATION: Not applicable

# **SECTION 5—FIREFIGHTING MEASURES**

FLAMMABLE PROPERTIES: Not applicable

**EXTINGUISHING MEDIA:** Not applicable

PROTECTION OF FIREFIGHTERS: Not applicable

#### SECTION 6—ACCIDENTAL RELEASE MEASURES

Not applicable

# **SECTION 7—HANDLING & STORAGE**

# RECOMMENDED STORAGE

No special requirements

# PROCEDURES FOR HANDLING

Proper hand and foot protection is recommended.

## SECTION 8—EXPOSURE CONTROLS/ PERSONAL PROTECTION

#### **ENGINEERING CONTROLS**

None Required. There are no health hazards from castings in solid form.

SUBSTANCE	ACGIH TLV mg/m <sup>3</sup>	OSHA PEL mg/m³ N/e	
Carbon (C)	N/E		
Chromium (Cr)	0.5		
Iron (Fe)	N/E	N/E	
Manganese (Mn)	0.02 (R); 0.1 (I)	5 (C)	
Molybdenum (Mo)	N/E	N/E	
Nickel (Ni)	1.5 (I)	. 1	

Page 2 of 6

Silicon (Si)		
Total dust	N/E	15
Respirable dust	N/E	5

#### SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica. Fumes from hot processes may contain other compounds with different exposure limits than those listed above. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls. In particular, Hexavalent Chromium is an OSHA Expanded Health Standard; refer to OSHA 29 CFR 1910.1026- Chromium (VI) for complete requirements.

SUBSTANCE	ACGIH TLV mg/m <sup>3</sup>	OSHA PEL mg/m <sup>3</sup>
Chromium Compounds,(as Cr)		
Chromium (II) inorganic compounds	N/E	0.5
Chromium (III) inorganic compounds	0.5	0.5
Chromium (VI) inorganic compounds, certain water insoluble	0.01	0.005
Chromium (VI) inorganic compounds, water soluble	0.05	0.005
Chromium (VI) all forms and compounds	N/E	0.005
Iron Compounds		
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) fume	N/E	10
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )	5 (R)	N/E
Molybdenum Compounds (as Mo)		
Insoluble compounds (as Mo)	10 (I); 3 (R)	N/E
Soluble compounds (as Mo)	0.5 (R)	5
Total Dust	N/E	15
Nickel Compounds (as Ni)		
Insoluble, inorganic compounds	0.2(1)	1
Soluble, inorganic compounds	0.1(I)	1
Nickel oxide	0.2(1)	1

#### **TERMS**

All exposure limits referenced above are 8 hour time weighted averages (TWA) unless otherwise noted.

N/E = None Established

C = Ceiling

I = Inhalable fraction

R= Respirable fraction

TLV = Threshold Limit Value/ACGIH (American Conference of Industrial Hygienists)

PEL = Permissible Exposure Limit/OSHA (Occupational Safety & Health Administration)

STEL= Short Term Exposure Limit

mg/m<sup>3</sup> = milligrams per cubic meter

## PERSONAL PROTECTION

Proper hand and foot protection is recommended.

# **SECTION 9—PHYSICAL & CHEMICAL PROPERTIES**

#### APPEARANCE/PHYSICAL STATE

Solid, silver gray in color

ODOR/ODOR THRESHOLD	VAPOR DENSITY
None	Not applicable
MELTING POINT/FREEZING POINT 2744-3199°F (1504-1704°C)	SPECIFIC GRAVITY (Relative Density) 0.28 lb/in³ (7.74 g/cm³) for cast alloy steels
BOILING POINT 5000°F (2750°C) for iron	VAPOR PRESSURE  Not applicable
FLASH POINT  Not applicable for solid castings	EVAPORATION RATE  Not applicable

FLAMMABILITY Not flammable	SOLUBILITY IN WATER Insoluble
UPPER AND LOWER FLAMMABILITY LIMITS  Not applicable for solid castings	pH Not applicable
AUTO IGNITION TEMPERATURE  Not applicable	VISCOSITY  Not applicable
DECOMPOSITION TEMPERATURE  Not applicable	PARTITION COEFFICIENT  Not applicable

# SECTION 10—STABILITY & REACTIVITY

#### CHEMICAL STABILITY

Stable

## **CONDITIONS TO AVOID**

None

110110	
REACTIVITY	INCOMPATIBLE MATERIALS
Not reactive	None
HAZARDOUS DECOMPOSITION PRODUCTS	POSSIBILITY OF HAZARDOUS REACTIONS
- None	Not applicable

## SECTION 11—TOXICOLOGICAL INFORMATION

## POTENTIAL HEALTH EFFECTS

**EYE CONTACT:** None SKIN: None

INGESTION: None

**INHALATION:** None

#### **Carcinogen Classification of Ingredients**

INGREDIENT	OSHA	NTP	IARC	TARGET ORGAN
Nickel (metal)	NL	K	2B	Lung, Nose

#### **TERMS**

# OSHA—Occupational Safety & Health Administration

Y = Listed as a Human Carcinogen

## NTP—National Toxicology Program

K = Known to be a Human Carcinogen

R = Reasonably Anticipated to be a Human Carcinogen (RAHC)

## IARC—International Agency for Research on Cancer

1 = Carcinogen to Humans

2A = Probably Carcinogenic to Humans

2B = Possibly Carcinogenic to Humans

3 = Unclassifiable as to Carcinogenicity in Humans

4 = Probably not Carcinogenic to Humans

#### Other

NL = Not Listed

## **SECTION 12—ECOLOGICAL INFORMATION** PERSISTENCE AND DEGRADABILITY Not applicable **MOBILITY IN SOIL BIOACCUMULATION POTENTIAL**

Not applicable

#### OTHER ADVERSE EFFECTS

Not applicable

**ECOTOXICITY** 

Not applicable

Not applicable

#### **SECTION 13—DISPOSAL CONSIDERATIONS**

Recover or recycle if possible. Dispose of according to federal, state and local regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult federal, state and local regulations.

SECTION 14—TRANSPORT INFORMATION		
US DEPARTMENT OF TRANSPORTATION (DOT)-HMR (Hazardous Materials Registration) Not Regulated	CANADIAN TRANSPORTATION OF DANGEROUS GOODS (TDG) Not regulated	
UN SHIPPING NAME  Not regulated  TRANSPORT HAZARD CLASS	UN NUMBER Not regulated PACKING GROUP	
Not regulated	Not regulated	
ENVIRONMENTAL HAZARDS None	LABEL(S) REQUIRED? No	
TRANSPORT IN BULK Not applicable	SPECIAL SHIPPING INFORMATION  Not applicable	

#### **SECTION 15—REGULATORY INFORMATION**

#### **US-OSHA (Hazard Communication Standard)**

Reference 29 CFR 1910.1200 and 1910.1000. A finished casting is an article as defined in the OSHA Hazard Communication Standard 29CFR 1910.1200 (c). Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as chromium, iron, manganese, molybdenum, nickel, silicon, and silica.

For hexavalent chromium references see 29 CFR 1910.1026.

#### **US-EPA (Toxic Substances Control Act-TSCA)**

All components of these products are on the TSCA inventory list or are excluded from listing.

#### **US-EPA (SARA Title III)**

Releases to the environment of **Chromium**, **Manganese and Nickel**, may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 72.

#### **CANADA-WHMIS (Workplace Hazardous Materials Information System)**

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

## **CANADA DSL (Domestic Substance List) Inventory Status**

All components of these products are on the DSL Inventory.

#### **CEPA (Canadian Environmental Protection Act)**

Chromium and nickel are on the CEPA Priorities Substances Lists

#### EINECS No. (European Inventory of Existing Commercial Chemical Substances)

All components of these products are on the EINECS list.

## RoHS (Restriction of Certain Hazardous Substances) Compliance

Castings comply with RoHS

# **CALIFORNIA PROPOSITION 65 Compliance**

WARNING: This product contains or produces chemicals known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code 25248.5 et seq.)

#### **US STATE REGULATORY INFORMATION**

Some of the components listed in Section 3 may be covered under specific state regulations.

SECTION 16—	OTHER INFORMATION	ON
SDS SHEET PREPARED BY	DATE	
American Foundry Society, Inc.	10/13	
Occupational Safety & Health Committee (10-Q)		

#### NOTE

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

Addendum: Label Information

# **PRODUCT IDENTIFIER**

SC 000-009 Rev. 16

# **CARBON & ALLOY STEEL CASTINGS**

SUPPLIER IDENTIFICATION	HAZARD PICTOGRAMS
Company Name Sawbrook Steel LLC	None*
Street Address 425 Shepherd Ave.	
Mailing Address: P.O. Box 15527	SIGNAL WORD
City Cincinnati State OH	None*
Zip/Postal Code 45215-0527 Country USA	
Emergency Phone Number (513) 554-1700	
Other Info	•
	, b
PRECAUTIONARY STATEMENTS	HAZARD STATEMENTS
None*	None*

\*Castings do not present hazards in their original form.

#### OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.